Product Details

1.□□□CSC5160GYYDX5
2.□□□□□Kg□□16000
3.□□□□□4 * 2
4.□□□□□Kg□□9800
5.□□□□□mm□□8990 * 2380 * 3180
6.□□□mm□□4700
7.□□□□□DFL1160BX5
8.□□□□□Euro4
9.□□□□□L /m³□□16

Product Display

汽油
www.mioutruck.com

汽油
www.mioutruck.com

Technical Parameter

□□□□□□			
□□□□	CSC5160GYYDX5		
□□□□□Kg□	16000	□□□□	4 * 2
□□□□□Kg□	9800	□□□□□mm□	8990×2380×3180
□□□□□Kg□	6005	□□□□□□□□□□	3
□□/□□□□	12/19	□□□□□mm□	1430/2860
□□	2	□□□mm□	4700
□□□Kg□	6000/10000	□□□□□Km / h□	80
□□□□			
□□□□	DFL1160BX5	□□□□□mm□	7190×2370×2760
□□□□	9.00R20	□□□	6
□□□□	8/10 + 8	□□□□mm□	1880
□□□□	desile	□□□□mm□	1860
□□□□	Euro4	□□□	6 □

[illegible]	D530[illegible]		
[illegible]	[illegible]	[illegible]ml[illegible]	[illegible]Kw[illegible]
ISB180 40	[illegible]	5900	132
[illegible]L / m 3[illegible]	16		
[illegible]	Q235[illegible]		
[illegible]	[illegible] [illegible]		
[illegible]			

A[illegible];

B[illegible];

C[illegible]15[illegible];

D[illegible] ;

E[illegible]1-3[illegible]

[illegible] [illegible]

[illegible] [illegible]

[illegible]

□□□□

Verified Certificates

□□: □□□□□□□□□□□□□□□□ 20' GP □ 40' GP□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□: 15 □

[illegible]

[illegible]

[illegible]ISO[illegible]

[illegible]

[illegible]

[illegible]15[illegible]30[illegible]

[illegible]

[illegible]

[illegible]

[illegible]3000[illegible]

[illegible]

[illegible]ISO CCC[illegible]BV[illegible]

[illegible]

[illegible]

[illegible]

[illegible]1[illegible]

[illegible]

[illegible]T / T[illegible]L / C[illegible]

[illegible]

[illegible]

[illegible]!

[illegible]:

[illegible]

[illegible]

Hubei Miou Special Automobile Technology Co.,Ltd

Name:Lincy

Post: Sales Representative

Email:lincy@chinasonglin.cn

Tel:+8613597902165

QQ:2853937064

Website:www.mioutruck.com