

## Product Details

产品型号:

底盘型号: DFL1160BX1  
 清扫器型号: YSY5160TSL  
 清扫宽度: 16000 清扫速度: 0-1000, 可调

## Product Display



## Technical Parameter

|       |                  |
|-------|------------------|
| 轴距    | 4 * 2 轴距 2000 mm |
| 清扫器型号 | YSY5160TSL       |
| 底盘型号  | DFL1160BX1       |

|                             |                |  |                    |  |
|-----------------------------|----------------|--|--------------------|--|
| □□                          | □□ □□          | mm                                     | 7030 × 2435 × 3030 |  |
|                             | □ □□           | kg                                     | 16000              |  |
|                             | □□ □□          |  | 8880               |  |
|                             | □ □ □ □ F/R    | mm                                     | 1430/1880          |  |
|                             | □□ □□          |  | 3800               |  |
|                             | □□□□ □□        | 4 * 2                                  |                    |  |
|                             | □□□ □          | 2                                      |                    |  |
|                             | □□ □ leafs     | 7 / 9 + 6, 8 / 10 + 8                  |                    |  |
|                             | □□□ □□         | 9.00-20 9.00 R 20 10.00-20, 10.00R20   |                    |  |
|                             | □□□□ □         | 6                                      |                    |  |
|                             | □□□□ □□ □□□ □□ | 2                                      |                    |  |
|                             | □□             | □□ □□                                  | ISDe210 30         |  |
|                             |                | □□□ □□                                 | □□                 |  |
| □□□/□□                      |                | ml/hp                                  | 6700/210           |  |
| □□ □□                       |                | Km/h                                   | 90                 |  |
| □□ standard(TAS)            |                | □□ 3                                   |                    |  |
| □□ □□ □□ □ □□ □□            | □□ □□          | □ □□ 4 □ □□□ □□ □□ □. □□ □ □ □□ □□□□□. |                    |  |
|                             | □□ □□          | □□□□□ □□□ □□, □□ □ □ □□ □□□ □□□        |                    |  |
|                             | □□ □□          | □□ □ (mm) □□                           | 2000               |  |
|                             |                | □□ □□ (m <sup>2</sup> /h) □□           | 30000              |  |
|                             |                | □□ □□                                  | 90%                |  |
|                             |                | □□ □□ (km/h) □□                        | 20                 |  |
|                             |                | □□ □ □□ (°)                            | ≥45                |  |
|                             |                | □□ □□ □□ (mm)                          | 55                 |  |
|                             |                | □□□ □□ □□ (m <sup>3</sup> )            | 4                  |  |
| □ □□ □ □□ (m <sup>3</sup> ) | 0.8            |  |                    |  |

## Our Company & Factory

□□ □ □□:

□□□ □ □, □□□ □□□ □□ □ □, □□ □□□ R & D, □□, □□ □□ □□ □□□ □□□. □□□ □□ □□ □ □ Zhengmeng □□ □□ □□ Co., □□ □□ □□ □ □ □□□ □□□ □□ □ □□ □□ □□ □□

□□ □□□□□:



□ □ □ □ □ □ :



Verified Certificates



## Package & Shipment

□□ □□ □□□:  
□□ □□: 7-10 □  
□□ □□: 30 %TT □□□ 70% TT b/L □□ □□ □□□  
□□: □□, □□, □□□ □□ □ □□□□ 20' GP 40' GP, □□□ □□ □□□□ □□ □□ □□ □□ □□ □□ □□ □□.

