

Product Details

洒水车

驱动形式:	4x2	轴数:	2	排放标准:	Euro 3
轴距:	3000	车身长度 (M):	12 - 16	罐体尺寸 (mm x mm x mm):	8160x2480x2710
容量:	4 - 6L	重量:	10001 - 15001L	配置:	YTZ5160GSS20E
品牌:	Dongfeng	座位数:	132		

Product Display



Technical Parameter

名称	型号
洒水车型号	YTZ5160GSS20E
底盘型号	EQ1168KJ
生产厂家	Dongfeng 东风 Co. , Ltd.

ISDe180 30	ISDe180 30
132	132
Kerb (mm)	7355
(kg)	16000
(mm / mm)	90
gradeability (%)	30
(M)	≤18
(mm)	≥248
(°)	≥25
(°)	≥11
(m ³)	10
(mm)	≥14
(M)	≥35
(mm / mm)	5-20
(M)	90
(m ³ /mm)	60
(mm)	& lt; 5
(M)	& gt; 6.5
	10.00-20

Our Company & Factory

Miou Shiyuan, R & D, Dongfeng Motor, Dongfeng Zhengmeng

:



Package & Shipment

包装: 20'GP 40'GP RO-RO
数量: 15 个



FAQ

Q: 請問...

A: 請問...

Q: 請問... ISO?

A: 請問...

Q: 請問...?

A: 請問... 15 ... 30 ...

Q: 請問...?

A: 請問... RORO ...

Q: 請問...?

A: 請問... 3000 ...

Q: 請問...?

A: 請問... workshop ... ISO CCC BV ...

Q: 請問...?

A: 請問...

Q: 請問...? ... MOQ ...?

A: 請問... MOQ ... 1 ...

Q:

A:

Q:

A:

Contact us