

Product Details

G.V.W: 4290kgs

□□□□□ / □□□□□□□□ angle:22/14(°)

□□□□: 1880/2410

□□□□/□□□□ suspension:1320/1375,1320/1575,1320/1025(mm)

Product Display





Technical Parameter

外廓尺寸	5995×2290,2100×2800,2550(mm)
整备质量	4290(Kg)
额定载质量	2600(Kg)
最大爬坡度	22/14(°)
轴距	1880/2410
轴数	2
最小转弯半径	12.1
轮胎规格	7.00-16LT 8PR, 7.00R16LT 8PR, 7.50-16LT 6
轮胎数	6
前悬/后悬	1835,1750
轮距	1640,1585
轴距/轴距	3700,4200,3880,4050×2100,2200,2130,1950×550,600,450(mm)
整备质量	1495(Kg)
ABS	有
前悬/后悬	1320/1375,1320/1575,1320/1025(mm)
轴距	3100,3300,3650(mm)
最高车速	90(km/h)
档位	6 / 6 + 5, 8 / 10 + 7

Our Company & Factory



Verified Certificates



Package & Shipment

□□□□□□: □□□□□□ □□□□□□ □□□□□□□□□□ □□□□□□□□□□□□□□□□□□ □□□□ 20' GP □□□□ 40' GP

ro ro

15



FAQ

Question 1

A: Answer 1

Question 2 ISO

A: Answer 2

Question 3

Question 3 details: 15 30

Question 4

Question 4 details: RORO Pls

Question 5

A: Answer 5 3000

Milla Nong

TEL/Whatsapp : +8618772815090

Email : Chinatruck@chinasonglin.cn

Web:www.mioutruck.com

SKYPE : Milla Nong

