

Product Details

Q1111 11 11:

11: 111 11: 11 11 11 11: 11
1111 11: 6 X 2 11 11: 11 4 1111 11: 6 × 2, LHD (RHD)
1111 11: 1 1 11 11: 11 1111 11: 3

Product Display





Technical Parameter

长/宽/高 length/width/height(mm)	8450 x 2400 x 3150
整备质量 Mass(kg)	25000
自重 (kg)	11905
载重 load(kg)	12900
最高车速	90
最高 speed(km/h)	90
挡位数	6
驱动形式	6 × 2, LHD (RHD)
轴数	3
F/R 轴重 (kg)	7000/7000/11000
轴距 (mm)	1850 + 2850
前悬 (mm)	1750/1750
后悬 (mm)	1750
最小转弯半径 (°)	34/29
F/R 轴距 (mm)	1400/1650

缸径 mm	8	
缸径 mm	10.00R20, 11.00 R 20	
缸径 mm	9/9/10 + 8	
缸径	8 缸径, 2 缸	
缸径	Uniwafer, 缸径 缸径, 缸径 缸径 缸径	
缸径 缸径	缸径 缸径	
缸径	缸径 缸径	
缸径	YC6J180 + 42	YC4EG180-40
缸 Power(hp)	180	180
Displacement(cc)/Power(kw)	6500/132	4730/132
缸径	缸径 4	

Our Company & Factory

缸径 缸径:

缸径 缸径, 缸径 缸径 缸径 缸径, 缸径 缸径 R & D, 缸径, 缸径 缸径 缸径 缸径 缸径. 缸径 缸径 缸径 缸径 Zhengmeng 缸径 缸径 缸径 Co., 缸径 缸径 缸径 缸径 缸径 缸径 缸径 缸径 缸径 缸径 缸径 缸径

缸径 缸径缸径:



缸径 缸径缸径:



Verified Certificates



Package & Shipment

☎: ☎, ☎ ☎, ☎ ☎☎ ☎ ☎ ☎☎☎ 20' GP 40' GP, ☎ ☎ ☎ ☎ ☎ ☎ ☎☎ ☎☎ ro ro ☎ ☎ ☎ ☎☎ ☎ ☎ ☎☎
☎ ☎: 15 ☎



Contact us

☎☎ ☎☎ ☎☎☎ ☎, ☎☎ ☎☎ ☎☎, ☎☎ ☎ ☎☎ ☎☎!

☎ ☎:

☎ ☎☎ ☎☎ ☎☎ ☎ ☎☎. ☎☎ ☎☎ ☎☎ ☎☎ ☎ ☎ ☎ ☎☎☎ ☎☎ ☎☎ ☎☎ ☎☎ ☎ ☎☎☎.
☎ ☎☎ ☎☎ ☎☎ ☎ ☎☎ ☎☎, ☎☎ ☎ ☎☎ ☎☎☎. ☎☎ ☎☎ ☎☎☎ ☎ ☎☎ ☎☎☎. ☎☎ ☎ ☎☎☎ ☎☎ ☎☎☎ ☎☎☎ ☎.

Christina (Sales Manager)

Skype : 494397183@qq.com

Tel: +86-0719-8319942

Mobile: +86-15107178396

Website: www.mioutruck.com

