## Product Details

### **Quick Details**

Feature: Truck Crane Condition: New Application: all rotation
Rated Loading Capacity: 15T Rated Lifting Moment: 15.7TM Max. Lifting Load: 6.3T

Max. Lifting Height: 11m Span: 11m Place of Origin: Hubei, China

# Product Display





# Technical Parameter

Dali truck mounted crane           outside dimension (L×W×H)(mm)         9000×2500×3460           Cargo body size (L×WxH)(mm)         5600*2294*600 white color           Total mass(kg)         18,025           Loading mass(kg)         10,000           Kerb mass(kg)         7,800           Chassis Model /Manufacturer         DFL1160BX           driving type         4×2           Cabin         With one bed           Wheelbase (mm)         4700           Engine           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10,00-20					
Cargo body size (LxWxH)(mm)         5600*2294*600 white color           Total mass(kg)         18,025           Loading mass(kg)         10,000           Kerb mass(kg)         7,800           Chassis Model /Manufacturer         DFL1160BX           driving type         4×2           Cabin         With one bed           Wheelbase (mm)         4700           Engine           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Dali truck mounted crane				
Total mass(kg)	outside dimension (L×W×H)(mm)		9000×2500×3460		
Loading mass(kg)   10,000     Kerb mass(kg)   7,800     Chassis Model /Manufacturer   DFL1160BX     driving type   4×2     Cabin   With one bed     Wheelbase (mm)   4700	Cargo body size (L×W×H)(mm)		5600*2294*600 white color		
Kerb mass(kg)         7,800           Chassis Model /Manufacturer         DFL1160BX           driving type         4×2           Cabin         With one bed           Wheelbase (mm)         4700           Engine           Model         B190 33           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Total mass(kg)		18,025		
Chassis Model /Manufacturer         DFL1160BX           driving type         4×2           Cabin         With one bed           Wheelbase (mm)         4700           Engine           Model         B190 33           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Loading mass(kg)		10,000		
driving type         4×2           Cabin         With one bed           Wheelbase (mm)         4700           Engine           Model         B190 33           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Kerb mass(kg)		7,800		
Cabin         With one bed           Wheelbase (mm)         4700           Engine           Model         B190 33           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Chassis Model /Manufacturer		DFL1160BX		
Wheelbase (mm)         4700           Engine           Model         B190 33           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	driving type		4×2		
Engine           Model         B190 33           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Cabin		With one bed		
Model         B190 33           Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Wheelbase (mm)		4700		
Max. power/rotated speed         140(KW) /2500(rpm)         Max. torque         670(N.m) /1300-1500(rpm)           Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Engine				
Cylinder bore×Stroke(mm)         102×120         Displacement(ML)         5900           Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Model		B190 33		
Type of fuel         diesel         Company of engine         Dongfeng           Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Max. power/rotated speed	140(KW) /2500(rpm)	Max. torque	670(N.m) /1300-1500(rpm)	
Compression ratio         (17.3±0.5):1         Emission level         Euro 3           Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Cylinder bore×Stroke(mm)	102×120	Displacement(ML)	5900	
Chassis           Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Type of fuel	diesel	Company of engine	Dongfeng	
Front axle         4.5T           Rear axle         9T           Tyre         10.00-20	Compression ratio	(17.3±0.5):1	Emission level	Euro 3	
Rear axle         9T           Tyre         10.00-20	Chassis				
Tyre 10.00-20	Front axle		4.5T		
	Rear axle		9T		
M C	Tyre		10.0	10.00-20	
мах 5ρееα(кт/п) 90	Max Speed(km/h)		90		

# Our Company & Factory

### **Brief Introduction:**

Miou is located in Shiyan, Hubei province, China.Our company is specialized in R & D,manufacture and sales of special purpose vehicles .We are the special purpose vehicles production base company

of the Chinese Dongfeng Motor Group and also the Overseas Department of Dongfeng Zhengmeng Special Purpose Vehicle Co., Ltd.

## **Company Display:**



## **Factory Display:**





#### **Packaging Details:**

nude, covered with wax, small type can be put into 20'GP or 40'GP, big type can be carried by bulk carriersor ro-ro ship or according to your requirements

**Delivery Detail:** 15 days



## Contact us

## We provide you sincerely service if you have interest, contact us now!

### **REMARKS:**

The above information is just for your reference. We can manufacture the trucks as per your request and we can fulfill all your demands.

If you have any other questions or need any other information, please feel free to contact me. It would be my great pleasure to be on your service. Please check my contact information as following:

E-mail:caitlin@mioutruck.com

Mobile/WeChat/WhatsApp:+86 18154490468